



PRODUCT SPECIFICATION

Product: Jaga Play Low-H₂O.

Material

Brackets are included and made of sendzimir galvanised steel plate of 1 mm; supplied to be installed 190mm from each end.

The front panels: one piece casing, completely mounted, consisting of polyurethane lacquered 18mm thick MDF panels complete with anodised aluminium spacer rings.

Pencil proof grille on the underside of the casing at the top.

Outputs meet standard EN 442.

Heat Exchanger:

Shall be manufactured from seamless copper tubes, fitted with aluminium fins. The fins shall provide high contact area to the tubes, guaranteeing optimum efficiency, across a wide range of flow & return water temperatures. The heat exchanger shall be complete with 2No. brass ½" BSP connections. Generally these shall be same end connections except where specified to the alternative, and be suitable for left or right hand installation.

The complete heat exchanger assembly shall be non-corrosive and the whole assembly shall be electro statically lacquered with dirt repellent and dust proof anthracite grey epoxy polyester lacquer RAL 7024 gloss degree 70%.

The heat exchanger shall be supplied complete with ½" BSP air vent & ½" BSP drain plug, and the whole assembly to be pressure tested to 20 bar, with a maximum working pressure of 10bar. The heat exchanger shall be of sufficient quality to be provided with the manufacturer's 30 year guarantee.

Controls

The casing comes complete with premounted integrated controller mounted in the front panel in the right hand top corner.

Finish

The casing is in a scratch resistant and UV resistant structured soft structured matt polyurethane finish.

Options

Base grille to screen the underside of the casing.

Dynamic Boost Effect option to increase output.