



IGUANA CIRCO WALL-MOUNTED

Distinctively elegant vertical radiators



jaga


Outputs

Outputs in watts at 75/65/20°C & 55/45/20°C, in accordance with EN442

ORDER CODE: CIRW code height length colour connection
180 027 301 /MM

(Example order code shown is for a 1800mm high radiator, 270mm long)


H		L 270	310	340
1800	75/65/20	801	946	1092
	55/45/20	385	454	524
1920	75/65/20	854	1009	1164
	55/45/20	414	489	564
2000	75/65/20	887	1048	1209
	55/45/20	433	511	590
2200	75/65/20	961	1136	1311
	55/45/20	476	563	649
2400	75/65/20	1024	1210	1397
	55/45/20	515	609	703



Supplied as Standard

- Colours: 001 Sandblast grey metallic, 301 white or 333 traffic white
- Central connection MM underneath
- Wall fixing
- 2 chrome-plated air vents G 1/8"

Pressure drop



Weight & water content

Weight in kg


H	Ø	270	310	340
1800		28.7	33.8	39.0
1920		30.4	35.9	41.4
2000		31.6	37.3	43.0
2200		34.5	40.8	47.0
2400		37.7	44.4	51.3

Weight content in litre

H	Ø	270	310	340
1800		9.6	11.3	13.1
1920		10.2	12.1	13.9
2000		10.6	12.6	14.5
2200		11.7	13.8	16.0
2400		12.8	15.1	17.4


Options

Table in beech veneer




Diameter Ø	278mm Order code: 9087.012660	313mm Order code: 9087.012730	348mm Order code: 9087.012800
W	660	730	800
D	500	550	600

Large shelf in beech veneer




Diameter Ø	278mm Order code: 9087.010637	313mm Order code: 9087.010672	348mm Order code: 9087.010707
W	637	672	707
D	312	329	347

Small shelf in beech veneer




Diameter Ø	278mm Order code: 9087.011497	313mm Order code: 9087.011532	348mm Order code: 9087.011567
W	497	532	567
D	242	259	277

Towel rail chrome-plated aluminium



Diameter Ø	278mm Order code: 9087.013427	313mm Order code: 9087.013427	348mm Order code: 9087.013493
W	427	427	493
D	221	221	253

Hat rack chrome-plated aluminium



Diameter Ø	278mm Order code: 9087.014427	313mm Order code: 9087.014427	348mm Order code: 9087.014493
W	427	427	493
D	221	221	253

All dimensions in mm

Connection Sets


The order code of the connection set will be completed with the sleeve coupling code

Set 31

For connection to the wall

Two pipe

Code	Thermostatic head
CODE.MW2.MW.1...	white
CODE.MW2.MC.1...	chrome
CODE.MW2.MB.1...	black



Set 32

For connection to the floor

Two pipe



Code	Thermostatic head
CODE.MF2.MW.1...	white
CODE.MF2.MC.1...	chrome
CODE.MF2.MB.1...	black



Set 33

For connection to the wall

Two pipe



CODE.JW2.DW.1...	
CODE.JW2.DC.1...	



Set 34

For connection to the floor

Two pipe



CODE.JF2.DW.1...	
CODE.JF2.DC.1...	




Set 35

For connection to the wall

Two pipe

CODE.JH2.DW.1...	
CODE.JH2.DC.1...	



Thermostatic heads

DW



Chrome/ White

DC



Chrome

Connection Sets

The order code of the connection set will be completed with the sleeve coupling code

Set 41


For connection to the wall

Two pipe

CODE.PW3.DW.1...



CODE.PW3.DC.1...



Set 42

For connection to the floor


Two pipe

42 – Standard Kv

CODE.PF3.DW.1...




CODE.PF3.DC.1...




Set 43

For connection to the floor or to the wall / flow left

Code	Ø	
COIG.28L.DW.3...	27	
COIG.28L.DC.3...	27	
COIG.31L.DW.3...	31	
COIG.31L.DC.3...	31	
COIG.34L.DW.3...	34	
COIG.34L.DC.3...	34	



For connection to the wall
with set 43 and set 44:
order 2 curves




Curves 90° M24 x M24
Order code: 5095.020

Set 44

For connection to the floor or to the wall / flow right

Code	Ø	
COIG.28R.DW.3...	27	
COIG.28R.DC.3...	27	
COIG.31R.DW.3...	31	
COIG.31R.DC.3...	31	
COIG.34R.DW.3...	34	
COIG.34R.DC.3...	34	




Sleeve Couplings

Included in the price of the connection sets

For Jaga valve - M24


For flexible steel or copper tube

Code	Tube Ø
110	10/1
112	12/1
114	14/1
115	15/1
116	16/1
118	18/1




For RPE/ALU tube

Code	Tube Ø
314	14/2
316	16/2
326	16/2.2
318	18/2



Pro Key



Tool for easy mounting of the Jaga Pro valve.


Code 5090.1120

Complete ordering code with sleeve couplings according to the material used and diameter of the tube. *The correct type of sleeve coupling is determined by the ordering code of the connection set*

Example: COLO. PW2.DW. 32. (insert relevant code from above)


For synthetic tube

Code	Tube Ø
212	12/2
214	14/2
219	16/1.5
216	16/2
217	17/2
218	18/2



Steel tube for CH

Code	Tube Ø
501	1/2"
503	3/8"



Correction factors

Average correction factors according to EN442 - 75/65/20°C

TV	TL	TR_20	25	30	35	40	45	50	55	60	65	70	75	80	85
90	20	0.63	0.69	0.75	0.81	0.87	0.94	1.00	1.07	1.13	1.20	1.27	1.34	1.41	1.48
	24	0.54	0.59	0.65	0.71	0.77	0.83	0.90	0.96	1.03	1.09	1.16	1.23	1.29	1.36
85	20	0.57	0.63	0.69	0.75	0.81	0.87	0.94	1.00	1.07	1.13	1.20	1.27	1.34	1.41
	24	0.48	0.54	0.59	0.65	0.71	0.77	0.83	0.90	0.96	1.03	1.09	1.16	1.23	1.30
80	20	0.51	0.57	0.63	0.69	0.75	0.81	0.87	0.94	1.00	1.07	1.13	1.20		
	24	0.43	0.48	0.54	0.59	0.65	0.71	0.77	0.83	0.90	0.96	1.03	1.09		
75	20	0.46	0.51	0.57	0.63	0.69	0.75	0.81	0.87	0.94	1.00	1.07			
	24	0.37	0.43	0.48	0.54	0.59	0.65	0.71	0.77	0.83	0.90	0.96			
70	20	0.41	0.46	0.51	0.57	0.63	0.69	0.75	0.81	0.87	0.94				
	24	0.32	0.37	0.43	0.48	0.54	0.59	0.65	0.71	0.77	0.83				
65	20	0.35	0.41	0.46	0.51	0.57	0.63	0.69	0.75	0.81					
	24	0.27	0.32	0.37	0.43	0.48	0.54	0.59	0.65	0.71					
60	20	0.30	0.35	0.41	0.46	0.51	0.57	0.63	0.69						
	24	0.23	0.27	0.32	0.37	0.43	0.48	0.54	0.59						
55	20	0.26	0.30	0.35	0.41	0.46	0.51	0.57							
	24	0.18	0.23	0.27	0.32	0.37	0.43	0.48							
50	20	0.21	0.26	0.30	0.35	0.41	0.46								
	24	0.14	0.18	0.23	0.27	0.32	0.37								
45	20	0.16	0.21	0.26	0.30	0.35									
	24	0.13	0.17	0.22	0.26	0.31									
40	20	0.10	0.14	0.18	0.23	0.27									
	24	0.12	0.16	0.21	0.26										
35	20	0.06	0.10	0.14	0.18										
	24	0.08	0.12	0.16											
30	20	0.03	0.06	0.10											
	24	0.05	0.08												

The indicated outputs with ΔT 50°C and ΔT 30°C are the exact outputs. ΔT 50°C outputs are measured in accordance with EN442 and ΔT 30°C outputs are calculated according to EN442.

An average correction factor is given in this table for outputs at other ΔT and is applicable for all dimensions.

KEY
 Tv = flow temperature
 Tr = return temperature
 Tl = desired air temperature

How to choose the right radiator?

Rapid estimation of heat losses

Calculate the volume of the room (L x W x H) and multiply this by the Watts/m³ figure given in the table below. Choose according to the level of insulation and the desired room temperature.

Insulation	20°	24°
excellent	45	55
good	65	75
average	85	95
poor	100	115

Required output in Watts/m³

Example

Use the table to determine the relevant correction factor with a water temperature of 80/60°C with a room temperature of 24°C.

The correction factor = 0.90

Required output 1000 watts : 1000 divided by 0.90 = 1111 watts therefore search in this leaflet's standard output table for a product with an output of at least 1111 watts. Alternatively use the "Radiator Finder" search function on www.jaga.co.uk to identify all Jaga heating products with this required output.



Output calculated in accordance with EN442, at a water temperature of 75/65°C and a room temperature of 20°C ($\Delta T=50$).

Product description

Iguana Circo - wall-mounted

Material

Consists of vertical triangular steel radiation pipes, welded on steel positioning brackets. The radiation pipes are hydraulically connected using steel bends. Suitable for central heating.

Finish

The radiators are sandblasted, degreased, phosphated, electrostatically lacquered with epoxy-polyester powder and finally stove enamelled at 200 °C. This high quality finish offers an optimal scratch resistance and is very easy to maintain.

Thickness of the lacquer: min 80 µ

Pressure test: 9 bar

Working pressure: 6 bar

Colour

The radiator is lacquered in the colour sandblast grey metallic 001 / white (RAL 9010) / white (RAL 9016) / other (see colour chart)

The Iguana Circo wall mounted model consists of triangular vertical radiation pipes welded on steel positioning brackets. The radiation pipes are hydraulically connected using steel bends, placed next to each other in half a circle. Supplied with wall brackets and 2 air vents G 1/8". Central connection, standard for 2 pipe.

Options

All options have the same radius as the radiator. They can also be ordered and fitted afterwards.

- Towel rail and fixings in chrome-plated aluminium.
- Hat rack and fixings in chrome-plated aluminium- Including 5 coat hooks.
- Small shelf in beech veneer with chrome-plated fixings. Shelf width: 100mm.
- Large shelf in beech veneer with chrome-plated fixings. Shelf width: 170mm.
- Deco connection sets and valves 2 pipe.
- Table in beech veneer with supports and fixings in chrome-plated aluminium.
- Deco Pro connection sets and valves 2 pipe.
- Guard with thermostatic valve, return valve for invisible connection to the wall or to the floor. Floorboards need to be removed for the guard.
































How to install

The building services engineer chooses the heating elements considering the following conditions:

- A heat output calculation according to the standard.
- Tables of heat outputs and dimensions for Iguana Circo wall mounted radiators according to EN 442.
- The radiators will be mounted to the wall with accessory brackets.
- The specially designed thermostatic connection sets / thermostatic Jaga Deco / Jaga-Pro valves / manual Jaga Deco valves can be connected to plastic central heating service pipes / RPE/ALU. tube / copper tube/ steel pipe.
- Jaga thermostatic heads / Jaga Deco thermostatic heads chrome / Jaga Deco thermostatic heads chrome/ white / Jaga Comap thermostatic heads silver / not to be / to be fitted.

Jaga colours

For Iguana Circo - wall-mounted

 201 301 White	 212 312 Bahama	 222 322 Capri
 202 302 Off-white	 213 313 English Green	 223 323 Natural
 203 303 Light Grey	 214 314 Whisper Rose	 224 324 Edelweis
 204 304 Black	 215 315 Turquoise	 225 325 Jasmine
 205 305 Pergamon	 216 316 Bermuda	 226 326 Ruby Red
 206 306 Manhattan	 217 317 Chocolate Brown	 228 328 Classic White
 208 308 Sapphire Blue	 218 318 Azure	 229 329 Patina Green
 209 309 Dark Grey	 219 319 Violet	 230 330 Aloa Blue
 210 310 Golden Yellow	 220 320 Aegean	 231 331 Anthracite Grey
 211 311 Flaming Red	 221 321 Calypso	 232 332 Sunrise
		 233 333 Traffic White

Special Colours

 001 Sandblast Grey Metallic
 002 Hammerstroke Silver/Black
 003 Claret Metallic
 005 Smooth Grey Metallic
 006 Aluminium
 007 Anthracite Metallic
 008 Anthracite Structure

As it's impossible to reproduce colours with 100% accuracy, this colour chart is intended as a guide only. Colour swatches are available on request.

Jaga Guarantee Information

- 1** The guarantee is valid only if the equipment is properly and correctly used, by its first owner and if installed in accordance with the norms and instructions as detailed in the instruction leaflet and current industry standard practices.
- 2** The guarantee only applies to the equipment and the spare parts supplied by Jaga. Jaga has the choice between repair and replacement of the equipment or the spare parts. If any modifications have been made by Jaga to the standard product design, Jaga reserves the right to replace the guaranteed equipment with equivalent products or spare parts.
- 3** The period of guarantee is mentioned in this certificate. The guarantee decreases every year on a straight line basis by an equal percentage in order to reach a zero guarantee at the end of the guarantee period (e.g. for a period of 10 years the annual decrease of the guarantees 10% of the invoiced value). Repaired or replaced product is guaranteed through to the end of the original guarantee period.
- 4** The guarantee is valid only on products displaying the appropriate identification information concerning product type and series. No guarantee is granted on equipment or spare parts lacking this information, on equipment where this information has been removed or altered, or on equipment that has been repaired or modified by persons not authorised by Jaga to carry out this work.
- 5** The customer is responsible for any damage caused as a result of errors in installation or use of incorrect fittings, or for any damage caused by electrical connections, faulty or damaged electrical installations or appliances, erroneous voltage or hydraulic pressure and all other errors not directly related to the product delivered by Jaga. The guarantee is also revoked when unsuitable parts or components are used. The guarantee for our heat exchangers is not valid if they are regularly drained, or if they are heated by means of industrial water, steam or water saturated by excessive quantities of oxygen. The quality of the system after has to be in accordance with the VDI 2035-2 directives. The guarantee is also not applicable if the heat exchangers are placed in unsuitable atmospheric surroundings, such as but not exclusively ammonia, caustic substances etc.
- 6** This guarantee excludes damage due to incorrect handling and/or use of the equipment, or due to formation of lime deposits, incorrect use of the safety valve, or to all equipment that is incorporated into the building in a way that means it cannot be accessed normally.
- 7** Any work undertaken or product supplied as a result of a guarantee claim that proves not to be valid will be charged for. Product supplied will be invoiced at the customer's standard purchasing terms, and labour will be charged at £50 per hour with a minimum labour charge of £200.
- 8** The guarantee period starts from the date of the invoice for supply of the products covered by the guarantee. If the invoice is not available, the date of production will be used based on the product ID number/series.
- 9** Only the courts of judicial district Hasselt (Belgium) are authorised to deal with disputes arising from this guarantee. It will apply Belgian law even when sales involved are subjects of EU member states as well as non-EU member countries.

Casings and components

GUARANTEE
10
YEAR

Valves for Low-H2O heat exchangers

GUARANTEE
3
YEAR